

7929 Lincoln Ave. Riverside, CA 92504  
 Phone: 951.689.ICON Fax: 951.689.1016

PART #	DESCRIPTION
54100T	2007-UP FJ/4RUNNER TUBULAR UPPER TRAILING ARM KIT

COMPONENTS INCLUDED	
(2) 154300 07-UP FJ/4RUNNER TUBULAR UPPER TRAILING ARM (DRVR)	
HARDWARE INCLUDED	
(2) 295511 JM 12T ROD END F1 FIT (2) 605640 3/4-16 JAM NUT	(4) 157431 HEIM SPACER JM12 X .50 X 55MM (2) 297103 GREASELESS PRESS IN BUSHING 2.135 X 12.2MM X 54.75MM
TOOLS REQUIRED	
JACK JACK STANDS TORQUE WRENCH	1.25" OPEN END WRENCH 17MM SOCKET / WRENCH 21MM SOCKET / WRENCH
TECH NOTES	
<ol style="list-style-type: none"> <li>DO NOT EXCEED 2.0" FROM LINK FACE TO CENTERLINE OF ROD END.</li> <li>BUSHINGS ARE GREASELESS AND DO NOT REQUIRE MAINTENANCE.</li> <li>THE ROD END CAN BE MOUNTED AT AXLE END OR FRAME END.</li> </ol>	



**WARNING!**

**\*\* READ ALL INSTRUCTIONS THOROUGHLY FROM START TO FINISH BEFORE BEGINNING INSTALLATION! IF THESE INSTRUCTIONS ARE NOT PROPERLY FOLLOWED SEVERE FRAME, SUSPENSION AND TIRE DAMAGE MAY RESULT TO THE VEHICLE!**

**\*\* ICON VEHICLE DYNAMICS RECOMMENDS THAT YOU EXERCISE EXTREME CAUTION WHEN WORKING UNDER A VEHICLE THAT IS SUPPORTED WITH JACK STANDS.**

**\*\* ICON VEHICLE DYNAMICS RECOMMENDS ALL INSTALLTION TO BE PERFORMED BY A PROFESSIONAL SHOP/SERVICE TECHNICIAN. PRODUCT FAILURE CAUSED BY IMPROPER INSTALLATION WILL NOT BE COVERED UNDER ICON'S WARRANTY POLICY.**

### INSTALLATION

**1.** Using a properly rated jack, raise the rear of the vehicle and support the frame rails with jack stands. Ensure the jack stands are secure and set properly before lowering the jack. NEVER WORK UNDER AN UNSUPPORTED VEHICLE. Remove the rear wheels

**NOTE: REMOVE AND REPLACE ONLY ONE FACTORY LINK ARM AT A TIME.**

**2.** Lay ICON link arm over the factory link to set a starting point for adjustment (12.375").

**3.** Use the factory hardware to install the link arm on the axle end using a 17mm socket/wrench. [Torque to factory spec] [FIGURE 1 & 2]

FIG.1



FIG.2



4. The pinion angle can be adjusted as desired once both links are installed. Do not adjust longer than 2.0". [FIGURE 3]

FIG.3



5. Connect the link arm to the frame using the factory hardware. [FIGURE 4 & 5]

FIG.4



FIG.5



6. Tighten jam nut using an 1.25" open end wrench. [Torque to 120 ft-lbs] Make sure the rod end is vertical as it is tightened.

7. Tighten the front bolt on the lower link arm using a 17mm socket/wrench [Torque to factory spec]. Fasten emergency brake mount to the link arm with a 12mm socket/wrench using the factory hardware.

8. Repeat steps on the opposite side.

9. Reinstall wheels and lower vehicle to the ground. [Torque to factory spec]

***VERIFY ALL FASTENERS ARE PROPERLY TORQUED BEFORE DRIVING VEHICLE.***

***RETORQUE ALL NUTS, BOLTS AND LUGS AFTER 100 MILES AND PERIODICALLY THEREAFTER.***

## **ICON VEHICLE DYNAMICS LIMITED LIFETIME WARRANTY**

ICON Vehicle Dynamics warrants to the original retail purchaser who owns the vehicle on which the product was originally installed. ICON Vehicle Dynamics does not warrant the product for finish, alterations, modifications and/or installation contrary to ICON Vehicle Dynamics instructions. ICON Vehicle Dynamics products are not designed, nor are they intended to be installed on vehicles used in race applications, for racing purposes or for similar activities. (A "race" is defined as any contest between two or more vehicles, or a contest of one or more vehicles against the clock, whether or not such contest is for a prize). This warranty does not include coverage for police or taxi vehicles, race vehicles, or vehicles used for government or commercial purposes. Also excluded from this warranty are sales outside of the United States of America and Canada.

ICON Vehicle Dynamics' obligation under this warranty is limited to the repair or replacement, at ICON Vehicle Dynamics' discretion, of the defective product. Any and all costs of removal, installation or re-installation, freight charges and incidental or consequential damages are expressly excluded from this warranty. Items that are subject to wear are not considered defective when worn and are not covered.

ICON Vehicle Dynamics components must be installed as a complete kit as shown in our current application guide. Any substitutions or exemptions of required components will immediately void the warranty. Some finish damage may happen to parts during shipping and is not covered under warranty.

This warranty is expressly in lieu of all other warranties expressed or implied. This warranty shall not apply to any product that has been improperly installed, modified or customized subject to accident, negligence, abuse or misuse.

# **ICON VEHICLE DYNAMICS**

PERFORMANCE SUSPENSION SYSTEMS AND SHOCK ABSORBERS

7929 Lincoln Ave. Riverside, CA 92504 Phone: 951.689.ICON Fax: 951.689.1016  
[www.iconvehicledynamics.com](http://www.iconvehicledynamics.com)



**FOLLOW US ON FACEBOOK!**

